

Package: linkeR (via r-universe)

June 1, 2026

Title Link Interactive Plots and Tables in 'shiny' Applications

Version 0.1.4

Description Build powerful, linked-view dashboards in 'shiny' applications. With a declarative, one-line setup, you can create bidirectional links between interactive components. When a user interacts with one element (e.g., clicking a map marker), all linked components (such as 'DT' tables or other charts) instantly update. Supports 'leaflet' maps, 'DT' tables, 'plotly' charts, and spatial data via 'sf' objects out-of-the-box, with an extensible API for custom components.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Imports shiny (>= 1.5.0), magrittr (>= 2.0.0), later (>= 1.0.0)

Suggests leaflet, DT, sf, testthat (>= 3.0.0), knitr, plotly, bslib, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr

URL <https://epiforesite.github.io/linkeR/>,
<https://github.com/EpiForeSITE/linkeR/>

BugReports <https://github.com/EpiForeSITE/linkeR/issues/>

Config/pak/sysreqs cmake make libuv1-dev zlib1g-dev

Repository <https://epiforesite.r-universe.dev>

Date/Publication 2026-03-03 17:01:28 UTC

RemoteUrl <https://github.com/EpiForeSITE/linkeR>

RemoteRef HEAD

RemoteSha e4453062f1185a4125df50cf30af9bd65c6178c3

Contents

apply_default_leaflet_behavior	2
create_link_registry	3
diagnose_registry	5
link_plots	5
linkeR-imports	8
prepare_plotly_linking	8
register_dt	9
register_leaflet	10
register_plotly	12
setup_datatable_observers	13
setup_leaflet_observers	14
update_dt_selection	15
Index	17

apply_default_leaflet_behavior

Apply Default Leaflet Behavior for Selection Events

Description

apply_default_leaflet_behavior is a helper function that provides consistent default behavior for leaflet maps when handling selection events. It manages popup display and map navigation based on the selection state.

Usage

```
apply_default_leaflet_behavior(map_proxy, selected_data, component_info)
```

Arguments

map_proxy A leaflet map proxy object used to update the map

selected_data A data frame or list containing the selected row/item data. If NULL, indicates deselection occurred.

component_info A list containing component configuration information:

- shared_id_column** Character. Name of the column containing unique identifiers
- config** List containing:
 - lng_col** Character. Name of the longitude column
 - lat_col** Character. Name of the latitude column
 - highlight_zoom** Numeric. Zoom level to use when highlighting selection

Details

When `selected_data` is provided:

- Creates a popup with "Selected" header and ID information
- Sets map view to the selected location coordinates
- Applies the configured highlight zoom level

When `selected_data` is NULL (deselection):

- Removes all existing popups from the map

Value

Returns the modified map proxy object with updated view and popups

`create_link_registry` *Create a Link Registry for 'shiny' Component Coordination*

Description

`create_link_registry` creates a registry system that manages linked interactions between multiple 'shiny' components, allowing them to share selection state and coordinate their behavior.

Usage

```
create_link_registry(session, on_selection_change = NULL)
```

Arguments

<code>session</code>	A 'shiny' session object, required for server-side reactivity
<code>on_selection_change</code>	Optional callback function that gets called when selection changes. Should accept parameters: <code>selected_id</code> , <code>selected_data</code> , <code>source_component_id</code> , and <code>session</code>

Details

The registry maintains a shared state across all registered components, automatically setting up observers to synchronize selections. When a selection changes in one component, all other registered components are updated to reflect the same selection.

Components are automatically cleaned up when re-registered to prevent memory leaks from orphaned observers.

Value

A link_registry object with the following methods:

register_component(session, component_id, type, data_reactive, shared_id_column, config) Register a new component with the registry. Parameters:

- session: 'shiny' session object for namespacing. Can be global session in non-modular apps.
- component_id: Unique string identifier for the component
- type: Component type (e.g., "table", "plot")
- data_reactive: Reactive expression returning the component's data
- shared_id_column: Name of the column used for linking selections
- config: Optional list of component-specific configuration

clear_all() Remove all registered components and reset shared state

set_selection(selected_id, source_component_id) Programmatically update the selection state

get_selection() Get current selection as list with selected_id and source

get_on_selection_change() Return the on_selection_change callback function

get_components() Get registry components info (for debugging)

get_shared_state() Get current shared state (for debugging)

See Also

[setup_component_observers\(\)](#) for component observer setup

Examples

```
# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create registry with optional callback
registry <- create_link_registry(
  session = session,
  on_selection_change = function(id, data, source, session) {
    message("Selection changed to ID: ", id, " from: ", source)
  }
)

# In a real app, you would register components like this:
# my_data <- reactive({ data.frame(id = 1:3, name = c("A", "B", "C")) })
# registry$register_component("table1", "table", my_data, "id")
# registry$register_component("plot1", "plot", my_data, "id")
```

diagnose_registry *Diagnostic function to debug linkeR observer issues*

Description

Add this to your server function to diagnose why observers might not be firing

Usage

```
diagnose_registry(registry, session)
```

Arguments

registry	The linkeR registry object
session	The Shiny session object

Examples

```
## Not run:
server <- function(input, output, session) {
  registry <- create_link_registry(session)

  # Register your components...

  # Add diagnostics
  diagnose_registry(registry, session)
}

## End(Not run)
```

link_plots *Simple Plot Linking Function for Non-Modular 'shiny' Apps*

Description

link_plots provides a simple, one-line interface to link interactive components in a **single-file or non-modular 'shiny' application**. It automatically detects component types and sets up bidirectional linking.

Usage

```
link_plots(
  session,
  ...,
  shared_id_column,
  leaflet_lng_col = "longitude",
```

```

leaflet_lat_col = "latitude",
leaflet_click_handler = NULL,
dt_click_handler = NULL,
plotly_click_handler = NULL,
on_selection_change = NULL
)

```

Arguments

session	The 'shiny' session object
...	Named arguments where names are component output IDs and values are reactive data frames. Each data frame must contain the <code>shared_id_column</code> . For leaflet maps: can be sf objects (coordinates auto-extracted) or regular data frames with longitude/latitude columns.
shared_id_column	Character string naming the column that contains unique identifiers present in all linked components.
leaflet_lng_col	Character string naming the longitude column for leaflet maps. Defaults to "longitude". For sf objects, this will be the name of the created column.
leaflet_lat_col	Character string naming the latitude column for leaflet maps. Defaults to "latitude". For sf objects, this will be the name of the created column.
leaflet_click_handler	Optional function that handles leaflet marker clicks. This will be used for both direct clicks and when other components select this marker. Function should accept (map_proxy, selected_data, session).
dt_click_handler	Optional function that handles DT row selections. This will be used for both direct clicks and when other components select this row. Function should accept (dt_proxy, selected_data, session).
plotly_click_handler	Optional function that handles plotly point clicks. This will be used for both direct clicks and when other components select this point. Function should accept (plot_proxy, selected_data, session).
on_selection_change	Optional callback function that gets called when selection changes. Function should accept parameters: (selected_id, selected_data, source_component_id, session)

Details

This function is the fastest way to get started with `linker` and is ideal for straightforward dashboards.

For more complex applications that use **'shiny' Modules**, you should use the more robust pattern of creating a central registry with `create_link_registry()` and passing it to your modules, where

you will call `register_leaflet()` or `register_dt()` directly. This preserves module encapsulation and leads to more maintainable code. See the `modularized_example` for a complete example of this pattern.

Value

Invisibly returns the created registry object

Examples

```
# This example is for a single-file app.
# For modular apps, please see the "Using linkeR with Modules" vignette.
if (interactive()) {
  library(shiny)
  library(leaflet)
  library(DT)

  # Sample data
  sample_data <- data.frame(
    id = 1:10,
    name = paste("Location", 1:10),
    latitude = runif(10, 40.7, 40.8),
    longitude = runif(10, -111.95, -111.85),
    value = round(runif(10, 100, 1000))
  )

  ui <- fluidPage(
    titlePanel("linkeR Example"),
    fluidRow(
      column(6, leafletOutput("my_map")),
      column(6, DTOutput("my_table"))
    )
  )

  server <- function(input, output, session) {
    my_data <- reactive({
      sample_data
    })

    output$my_map <- renderLeaflet({
      leaflet(my_data()) %>%
        addTiles() %>%
        addMarkers(
          lng = ~longitude,
          lat = ~latitude,
          layerId = ~id,
          popup = ~name
        )
    })

    output$my_table <- renderDT({
      datatable(my_data()[, c("name", "value")], selection = "single")
    })
  }
}
```

```

    })

    link_plots(
      session,
      my_map = my_data,
      my_table = my_data,
      shared_id_column = "id"
    )
  }

  shinyApp(ui, server)
}

```

linkeR-imports	<i>Package imports</i>
----------------	------------------------

Description

Package imports

prepare_plotly_linking	<i>Prepare Plotly for Linking</i>
------------------------	-----------------------------------

Description

Utility function to automatically add required parameters to a plotly object for reliable linking, regardless of plot structure (single/multiple traces).

Usage

```
prepare_plotly_linking(plotly_obj, id_column, source)
```

Arguments

plotly_obj	A plotly object created with plot_ly()
id_column	Character string: name of the ID column in the data
source	Character string: plotly source identifier

Value

Modified plotly object with linking parameters added

Examples

```

library(plotly)

# Sample data
df <- data.frame(
  id = 1:5,
  value = c(10, 20, 15, 25, 30),
  group = c("A", "A", "B", "B", "C")
)

# Create a plotly scatter plot
p <- plot_ly(
  data = df,
  x = ~value,
  y = ~id,
  color = ~group
)

# Prepare for linking (adds customdata and source)
p <- prepare_plotly_linking(p, "id", "my_plot")

# Print the plot object (for demonstration)
print(p)

```

register_dt

Register a DT DataTable Component

Description

register_dt registers a DT datatable for linking with other components.

Usage

```

register_dt(
  session,
  registry,
  dt_output_id,
  data_reactive,
  shared_id_column,
  click_handler = NULL
)

```

Arguments

session	'shiny' session object. The session from the module where the DT is used. This could be global session in non-modular apps.
registry	A link registry created by create_link_registry()

dt_output_id Character string: the outputId of your `DT::DTOutput`
data_reactive Reactive expression returning the data frame for the table
shared_id_column Character string: name of the ID column
click_handler Optional function: custom click handler for row selection, must have args (map_proxy, selected_data, session), overrides all default behavior

Value

NULL (invisible). This function is called for its side effects of registering the component.

Examples

```

# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create a registry
registry <- create_link_registry(session)

# Sample reactive data
my_data <- shiny::reactive({
  data.frame(
    id = 1:5,
    name = c("A", "B", "C", "D", "E"),
    value = 11:15
  )
})

# Register a DT component
register_dt(session, registry, "my_table", my_data, "id")

# Verify registration
print(registry$get_components())
  
```

register_leaflet *Register a Leaflet Component*

Description

register_leaflet registers a Leaflet map for linking with other components.

Usage

```

register_leaflet(
  session,
  registry,
  leaflet_output_id,
  
```

```

    data_reactive,
    shared_id_column,
    lng_col = "longitude",
    lat_col = "latitude",
    highlight_zoom = 12,
    click_handler = NULL
  )

```

Arguments

session	'shiny' session object. The session from the module where the DT is used. This could be global session in non-modular apps.
registry	A link registry created by create_link_registry()
leaflet_output_id	Character string: the outputId of your leafletOutput
data_reactive	Reactive expression returning the data frame for the map
shared_id_column	Character string: name of the ID column
lng_col	Character string: name of longitude column (default: "longitude")
lat_col	Character string: name of latitude column (default: "latitude")
highlight_zoom	Numeric: zoom level when highlighting (default: 12)
click_handler	Optional function: custom click handler for row selection, must have args (map_proxy, selected_data, session), overrides all default behavior

Value

No return value, called for side effects.

Examples

```

# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create a registry
registry <- create_link_registry(session)

# Sample reactive data
my_data <- shiny::reactive({
  data.frame(
    id = 1:5,
    name = c("A", "B", "C", "D", "E"),
    longitude = -111.9 + runif(5, -0.1, 0.1),
    latitude = 40.7 + runif(5, -0.1, 0.1)
  )
})

# Register a leaflet component
register_leaflet(session, registry, "my_map", my_data, "id")

```

```
# Verify registration
print(registry$get_components())
```

register_plotly *Register a Plotly Component*

Description

register_plotly registers a Plotly component for linking with other components. The default behavior uses plotly's built-in point selection highlighting, which is simple and works reliably across all plot types.

Usage

```
register_plotly(
  session,
  registry,
  plotly_output_id,
  data_reactive,
  shared_id_column,
  event_types = c("plotly_click"),
  source = NULL,
  click_handler = NULL
)
```

Arguments

session	Shiny session object
registry	A link registry created by create_link_registry()
plotly_output_id	Character string: the outputId of your plotlyOutput
data_reactive	Reactive expression returning the data frame for the plot
shared_id_column	Character string: name of the ID column
event_types	Character vector: plotly event types to listen for
source	Character string: plotly source identifier for event tracking
click_handler	Optional function: custom selection update handler. Function signature: function(plot_proxy, selected_data, session) where selected_data is the row from data_reactive() or NULL to clear selection.

Value

NULL (invisible). This function is called for its side effects.

Examples

```
# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create a registry
registry <- create_link_registry(session)

# Sample reactive data
my_data <- shiny::reactive({
  data.frame(
    id = 1:5,
    name = c("A", "B", "C", "D", "E"),
    value = 11:15
  )
})

# Register a plotly component
register_plotly(
  session,
  registry,
  plotly_output_id = "my_plot",
  data_reactive = my_data,
  shared_id_column = "id"
)

# Verify registration
print(registry$get_components())
```

setup_datatable_observers

Setup DataTable Observers

Description

setup_datatable_observers Sets up reactive observers for a DataTable component to handle user interactions and state changes. This function establishes the necessary event handlers for selection changes and synchronizes the component with the shared application state.

Usage

```
setup_datatable_observers(
  component_id,
  session,
  components,
  shared_state,
  on_selection_change,
  registry = NULL
)
```

Arguments

component_id	Character string. Unique identifier for the DataTable component.
session	'shiny' session object. The current 'shiny' session for reactive context.
components	List. Collection of UI components in the application.
shared_state	Reactive values object. Shared state container for cross-component communication.
on_selection_change	Function. Callback function to execute when table selection changes.
registry	List or NULL. Optional registry for component management. Defaults to NULL.

Details

This function creates reactive observers that monitor DataTable interactions and update the shared state accordingly. It handles selection events and ensures proper synchronization between the DataTable component and other application components.

Value

NULL. This function is called for its side effects of setting up observers.

setup_leaflet_observers

Setup Leaflet Map Observers

Description

setup_leaflet_observers creates two observers for handling Leaflet map interactions in a linked component system. The first observer handles direct marker clicks on the map, while the second observer responds to selection changes from other linked components.

Usage

```
setup_leaflet_observers(  
  component_id,  
  session,  
  components,  
  shared_state,  
  on_selection_change,  
  registry = NULL  
)
```

Arguments

component_id	Character string. The unique identifier for the Leaflet component.
session	'shiny' session object for the current user session.
components	List containing component configuration data including data reactivities and shared ID columns.
shared_state	Reactive values object containing selected_id and selection_source for coordinating selections across components.
on_selection_change	Function to call when selection changes (currently unused).
registry	Optional registry object with set_selection method for managing selections. If NULL, falls back to direct shared_state updates.

Details

The marker click observer:

- Extracts clicked marker ID from the click event
- Retrieves corresponding data row from the component's data
- Clears existing popups and applies click behavior (custom or default)
- Updates selection state through registry or direct shared_state modification

The selection response observer:

- Only responds to selections from other components (not self-selections)
- Updates the map visualization to reflect the new selection

Value

List containing two observer objects:

observer1	Handles marker click events on the map
observer2	Responds to selection changes from other components

update_dt_selection *Update DT Selection Based on Shared ID*

Description

update_dt_selection Updates the selection state of a DataTable (DT) component when a shared ID is selected or deselected from another linked component. This function handles both custom click handlers and default selection behavior.

Usage

```
update_dt_selection(  
  component_id,  
  selected_id,  
  session,  
  components,  
  namespaced_id = NULL  
)
```

Arguments

<code>component_id</code>	Character string. The ID of the DT component to update.
<code>selected_id</code>	The shared ID value to select. If NULL, deselects all rows.
<code>session</code>	'shiny' session object for the current user session.
<code>components</code>	List containing component configuration information, including data reactives, shared ID columns, and optional custom click handlers.
<code>namespaced_id</code>	Character string. The namespaced ID of the component, used for registry lookups. If NULL, it will be inferred from <code>session\$ns(component_id)</code> .

Details

The function performs the following steps:

- Validates that the DT package is available
- Retrieves current data from the component's reactive data source
- Validates that the shared ID column exists in the data
- Creates a DT proxy for programmatic table manipulation
- Finds the matching row based on the shared ID
- Executes either custom click handler or default selection behavior

Value

NULL (invisible). Function is called for side effects only.

Custom Click Handlers

If a custom click handler is provided in the component configuration (`component_info$config$click_handler`), it will be called with the DT proxy, selected data (or NULL for deselection), and session. Otherwise, default row selection/deselection is performed.

Index

`apply_default_leaflet_behavior`, [2](#)
`create_link_registry`, [3](#)
`create_link_registry()`, [6](#), [9](#), [11](#), [12](#)
`diagnose_registry`, [5](#)
`DT::DTOutput`, [10](#)
`link_plots`, [5](#)
`linkeR-imports`, [8](#)
`prepare_plotly_linking`, [8](#)
`register_dt`, [9](#)
`register_dt()`, [7](#)
`register_leaflet`, [10](#)
`register_leaflet()`, [7](#)
`register_plotly`, [12](#)
`setup_component_observers()`, [4](#)
`setup_datatable_observers`, [13](#)
`setup_leaflet_observers`, [14](#)
`update_dt_selection`, [15](#)